TimeCast

Historic Buildings in Miniature

TimeCast, Unit 5E, Centurion Park, Kendal Road, Shrewsbury, SY1 4EH, England

Tel: 01743 465676

Email: sales@timecastmodels.co.uk

Website: http://www.timecastmodels.co.uk

6/017 Railway Station Instruction Sheet



Based on a disused station at Naleumont, this model represents a typical rural railway station from southern Belgium.

Naleumont is situated in the scenic Ardennes area of Belgium near the towns of Arlon and Bastogne. Similar stations can be found throughout Belgium and northern France

The model is a mixed media kit which includes parts made from both acrylic polymer and white metal.

Parts List

Main Station Building (1 piece)
Flat Roofed Annex (1 piece)
Annex Building (1 piece)
4 x large chimneys (for Main Station Building)
1 x Small chimney (for Annex Building)

Assembly – Please read carefully <u>before</u> assembling the model

We recommend the use of either a super glue gel or two-part epoxy adhesive (such as Araldite) for assembling the model.

Check the fit of all parts before gluing them together.

Some parts may require a little cleaning up prior to assembly – small bubbles on the surface of the parts can be removed with the tip of a modelling knife.

Chimneys may need to be trimmed of any flash to fit the locations of the roof pieces. Check for fit before gluing the chimneys into position.

Any gaps between the parts can be filled with a modelling putty or filler such as Milliput.

We recommend the following sequence for assembling the model:

- Glue the Annex building to the right hand end of the Main Building. Ensure that it is glued centrally against the end wall.
- 2. Glue the flat roofed annex to the left hand end of the main building. Ensure that it is glued centrally against the end wall.
- 3. Glue the chimneys onto the spaces marked on the roof. Please refer to the photographs for the correct positions of the chimneys.



Naleumont Station Front View (platform side)

Painting

The acrylic polymer parts can be painted without any need to prime or undercoat. Metal parts should be undercoated before painting. We recommend the use of water-based acrylic paints and inks for painting TimeCast models. For reference, the original building was constructed of rendered brick and painted white.

Chimneys – brick red with pale grey lead flashing, and light brown rendered top sections.

Roof Tiles - dark brown

Drainpipes and guttering – light grey

Main doors - dark brown wood

Small doors on annexes – light grey

Window Frames - white



Naleumont Station Rear View

Health and Safety Notice

Parts made from Acrylic Polymer are non-toxic and safe to handle, however care should be taken when cutting or sanding to avoid breathing in any dust.

TimeCast models are not toys. They are not appropriate for children under 36 months of age due to the presence of small parts.